

Degreaser SB

LESONAL

Technical Data Sheet



January 2003

L4.02.01

Description The purpose of cleaning and degreasing is to remove residual grease, oil, wax, silicones, sand, etc.
If omitted, loss of adhesion or blistering will occur, therefore before sanding, and painting always clean the object with a degreaser.

Product & ancillary items

Product	Special solvents
Suitable for:	Cleaning and degreasing of: -Bare steel -Alluminium -Zinc-coated steel -Plastic parts -Primers, surfacers and fillers -All existing coatings including thermoplastic acrylics
Method of use:	Wet a clean cloth thoroughly with Lesonal Degreaser and degrease / clean the surface by rubbing steadily. Immediately thereafter take a new clean cloth and rub the surface dry Note: to avoid condensation use solvent borne degreasers always between 16 and 25 ° Celsius
Shelflife:	4 Years
Explanation batchnumbers	Example: 022 2 168 041 022 Production plant 2 Year of production 168 Day of production 041 Number of the batch made that day

Health & Safety Data: These products are intended for professional use only. Please refer to can labels and Safety Data Sheets concerned for more specific information. The user of these products is required to comply with the national laws pertaining to Health & Safety disposal.

The above information is given in good faith, but without warranty, as the final results are also dependent upon factors of use which are outside our control.